

"Express Mail" mailing label number: EL603083270US

Date of Deposit: July 30, 2001

I hereby certify that the attached Utility Patent Application Transmittal, Fee Transmittal (original and 1 copy), Specifications, Claims, Abstract, Drawings (5 pages), Combined Declaration and Power of Attorney and fee are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to Box PATENT APPLICATION, Assistant Commissioner For Patents, Washington, D.C. 20251

R. Michael West

R. Michael West July 30, 2001
(Signature)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Introductory Portion

Be it known that I, MICHAEL B. ALLEN, a citizen of the United States and a resident of Stockton, County of San Joaquin, State of California, have invented a new and useful

APPARATUS AND METHOD FOR IMPRESSING PATTERNS

IN A SLIP-FORMED CONCRETE WALL

of which the following is a specification.

Background of the Invention

1. Field of the Invention

The invention relates generally to devices for slip-forming concrete structures, such as divider walls, retaining walls, and other vertically extending barriers. More specifically, the invention pertains to an apparatus including one or more impression rollers, strategically positioned at the discharge

end of a slip-form, to impress aesthetic patterns on the sidewalls and on the top wall of the slip-formed structure, just after the structure has been formed and before the concrete has cured.

2. Description of the Prior Art

Concrete walls have long been employed in freeway construction, both as divider walls between opposing directions of traffic, and as retainer walls extending along the sides of the outermost freeway lanes. Concrete walls are also used as barrier walls along property lines, and as aesthetic features in industrial or commercial landscaping. The need for concrete walls also arises to prevent erosion along the periphery of man-made lakes, and along river banks and coast lines.

Historically, concrete forms have been constructed from plywood and restraining posts assembled on the wall site, to shape, size, and direct the wall. After the concrete has been poured into the form and has cured sufficiently, the form is disassembled and another form is constructed for the adjacent wall section. This process is both labor intensive, and slow, owing to the amount of construction and disassembly of forms which it necessitates.

A relatively recent development in the concrete wall construction industry, is the application of a technique known as slip-forming. Instead of constructing a form on site, a mobile slip form is used. The mobile slip form is mounted to the frame of a motorized vehicle. A guide line is laid out defining one edge of the wall to be formed. The frame of the vehicle includes fore and aft alignment rods, maintained in contingent relation with the guide line by the operator.

As the motorized vehicle progresses forwardly down the guide line, fresh concrete is continuously poured into the slip form. The slump and constituent materials of the concrete mix are such that multiple vibrators, immersed within the slip form, are necessary to ensure thorough consolidation of the mix. When the formed concrete emerges from the output, or trailing edge of the form, it has smooth sidewalls and a smooth top wall.

The need also exists for an apparatus which slip-forms a wall and concurrently creates patterns or impressions in both surfaces of the sidewalls and in the top wall.

The need also exists for an apparatus which includes an impression roller which is easily and quickly interchangeable with another impression roller, to create a wide variety of different patterns or impressions in a slip-formed wall.

The need further exists for a two-stage impression roller for use with an apparatus manufacturing a slip-formed concrete wall, which concurrently creates patterns or impressions both in the surface of a vertical sidewall portion and in the surface of an angled stem portion of the wall.

Lastly, the need exists for an impression roller for use with an apparatus manufacturing a slip-formed concrete wall, creating a substantially continuous pattern or impression which repeats along the extent of the wall.

Summary of the Invention

The present invention provides both an apparatus and a method for impressing three-dimensional patterns in the exposed surface of a slip-formed concrete wall.

At least one impression roller is provided at the discharge end of the slip form. The roller includes a rigid inner form, preferably right-circular cylindrical in configuration. The inner form has an axis of rotation, which is maintained in generally parallel relation to the exposed surface of the wall.

An outer layer or coating of resilient material, such as silicon, is provided on the outer surface of the inner form. Typically, the layer is pre-cast on a shallow, horizontal casting frame. The casting frame is provided with a lower surface, configured in an aesthetically pleasing pattern. The material is filled to the top edge of the frame, forming a lower patterned side and an upper flat side. After the layer of material has cured, the layer is removed from the casting frame. The flat side of the resilient layer is then adhesively applied entirely around the outer surface of the inner form of the roller, so that the patterned side

of the layer faces outwardly.

Virtually any pattern may be used, but typical patterns include a random arrangement of stones and mortar lines, a linear arrangement of bricks and mortar lines, and geometric designs comprised of straight or curved lines. The pattern may also include matching edge portions, along a vertical line extending from the top to the bottom of the impression roller. In this instance, the patterns along one mating edge of the layer match the patterns along the other mating edge of the layer.

The impression roller is preferably mounted to the same movable frame which supports and transports the slip-form. The roller is adjustably mounted to the frame, and positioned so that the outer peripheral portion of the roller depresses slightly into the outer surface of the wall just as the freshly-formed wall emerges from the slip-form. Owing to the surface engagement between the wall surface and the outer periphery of the impression roller, the roller rotates continuously with the relative movement between the roller and the slip-formed wall. As a consequence, successive portions of the uncured, wet concrete are impressed with a pattern which corresponds to the pattern on the impression roller.

The outer surface of the roller is continuously sprayed with a liquid release agent, so the wet concrete will not stick to the roller surface. Alternatively, a film material, such as VISQUINE, may be continuously rolled out over the surface of the wet concrete before the roller comes into contact with the exposed surface of the wall. In this way, the roller will not come into direct contact with the wet concrete, and the roller surface will not attract or become fouled with concrete. Later, after the concrete has at least partially cured, the film material is peeled from the wall and the impressed pattern is apparent.

If the pattern includes matching edges, the pattern will continuously and seamlessly repeat itself along the wall surface. Entirely different patterns may be used across the horizontal or vertical extent of the impression roller. Additional rollers may be used to impress patterns on opposing vertical wall surfaces, as well as upon the top wall surface. Also, a two-stage impression roller, having one surface parallel to the roller axis and another surface angled with respect to the roller axis, may be used to form

impressions simultaneously in a vertical wall and in its angled supporting foot portion.

These and other features of the invention will now be described in further detail in the drawings and the detailed description of the preferred embodiment to follow.

Brief Description of the Drawings

Figure 1 is a right rear perspective view of a slip-form machine fitted with the sidewall and the top wall impression rollers of the present invention;

Figure 2 is a perspective view showing the adjustable mounting arrangement for the three impression rollers and the slip-form;

Figure 3 is a side elevational view, particularly showing the top side roller and its adjustable mounting feature;

Figure 4 is a rear elevational view, showing the three impression rollers, the slip-form, and the slip-formed wall with its footing;

Figure 5 is a top plan view of the sidewall impression rollers, showing their adjustable mounting feature;

Figure 6 is a fragmentary perspective view of an end of an impression roller, showing an edge portion of the adhesively applied silicon layer partially peeled away;

Figure 7 is a top plan view of a sidewall impression roller, the release agent spray bar, and the slip-form;

Figure 8 is a top plan view of a sidewall impression roller, the VISQUINE roll, and the slip-form;

Figure 9 is a side elevational view of a random stone and mortar pattern impressed in a slip-form wall, the broken center line representing the location of the matching edges, where the trailing edge of the first rolled impression meets the leading edge of the second rolled impression;

Figure 10 is plan view of an alternative geometric pattern;

Figure 11 is a plan view of an alternative brick and mortar pattern;

Figure 12 is a plan view of yet another geometric pattern;

Figure 13 is a rear elevational view of a slip-formed wall, in which only a single impression
5 roller is used to provide a pattern in one sidewall; and,

Figure 14 is a rear elevational view of a tall slip-formed wall, showing a transition
impression roller placing a pattern on one sidewall and upon the supporting foot of the wall.

Detailed Description of the Preferred Embodiment

Turning now to Figure 1, the apparatus 11 of the present invention includes a frame 12,
supported for forward advancement over the ground by a number of continuous track drive feet 13. Because
various machines for slip-forming walls or vertical barriers are well known in the art, their structure and
operation will not be described in great detail herein. However, several key components are included in all
such machines in one form or another, and they will be generally described herein so as to further the
understanding of the overall operation of the present invention.

15 A concrete elevator 14 is located at the forward end of the apparatus. Concrete 16 is
delivered into the elevator 14 by means of a chute 17, extending from a concrete truck (not shown). The
consistency of this concrete is quite viscous, having approximately a 1 1/2" slump. In addition, the concrete
used for this application has a somewhat higher percentage of aggregate than the normal concrete mix. Both
of these factors ensure that when the concrete wall 18 or vertical barrier emerges from the slip-forming
20 process, the wall will be entirely self-supporting and cure without deformation.

A continuous supply of fresh wet concrete, delivered off the upper end of the elevator 14,
is fed into an entry end 19 of a slip-form assembly 21. Slip-form assembly 21 includes a pair of parallel
side wall forms 22 and 23, and a top wall form 24. Side wall forms 22 and 23 are spaced apart a distance

corresponding to the transverse dimension of concrete wall 18. Top wall form 24 is perpendicular to both of the side walls, and spans the transverse dimension between them.

5 A pair of side panels 26 and a pair of end panels 27 define an open top hopper, surrounding the entry end 19. The side and end panels are effective to confine and accumulate a sufficient amount of concrete so that the entry end of slip-form assembly 21 is maintained full of concrete at all times. Having a continuous oversupply of concrete present in the entry end, helps to ensure that the slip-formed concrete wall 18 will not contain side voids or internal air pockets. However, as the concrete mixture is very dry and it contains significant amounts of aggregate, manual agitation of the concrete within the slip-form is also necessary. An agitator, having an elongated mixing probe 28 shown in broken line in Figure 4, causes the dry concrete mixture to disperse and mix throughout the interior volume of the slip-form. Although the mixing probe of only a single agitator is shown in the drawings, multiple mixing probes and agitators are typically employed in commercial slip-form machines.

10
15 As the concrete fills the slip-form assembly, the apparatus 11 advances forwardly and continuously, along a predetermined path. For that purpose, a guide line 29 is vertically spaced from the ground, along the path which is desired for the concrete wall 18. The guide line may be laid out in any direction or fashion, so that straight, angled, or curved walls may be produced. Plural alignment rods 31, depending from the side of the apparatus 11, are maintained in contingent relation with guide line 29 as the apparatus advances forwardly.

20 The concrete wall formed by the process includes a first sidewall 32, an opposing, second sidewall 33, a top wall 34, and a footing 36. As the bottom edges of the slip form assembly 21 are maintained in vertically spaced relation from the ground, concrete 16 passing downwardly through the slip-form pushes outwardly from beneath the slip form, naturally forming the footing 36. The footing may be left with a rough, unfinished surface, which is later covered with dirt. A trench (not shown) may also be excavated beforehand, so that the footing rests within the trench below grade. By the time the concrete

reaches a discharge end 37 of the slip-form assembly 21, the concrete wall 18 is fully formed, self-supporting, and ready for curing. The concrete of the just-emerged wall is still wet, and has smooth vertical sidewalls and a smooth top wall.

5 The primary purpose of the present invention is to impress an aesthetic three-dimensional pattern into an exposed smooth surface of the slip-formed wall 18 before the concrete cures. To accomplish that purpose, sidewall impression rollers 38 and 39, and top wall impression roller 41 are provided. Impression rollers 38, 39 and 41 are all of substantially identical construction, although their sizes may vary with the particular application. Thus, in the discussion to follow, identical numerals will be used to identify identical structural elements for the various impression rollers.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
10145
10150
10155
10160
10165
10170
10175
10180
10185
10190
10195
10200
10205
10210
10215
10220
10225
10230
10235
10240

impression roller 38 are made. A substantially identical construction is provided at the lower end of roller 38, to provide lateral adjustments for support arm 49 and the lower end of roller 38.

Using the aforementioned adjustable support system, the positions of rollers 38 and 39 are set so that their outer peripheries 43 are partially depressed into an exposed surface of the wet concrete, as it emerges from the discharge end 37 of the slip form assembly 22. In addition, the axis of rotation 42 of rollers 38 and 39 are set so that it is substantially parallel to the adjacent exposed surface of the wall 18.

A similar arrangement is used to support top wall impression roller 41. One end of a pair of side support arms 45 supports roller 41 about its axis of rotation 42. An intermediate portion of the arms 45 is pivotally mounted to plates 56. A tensioning bolt 60 is provided at the end of each arm 45. Although gravity naturally presses impression roller 41 into the top wall to a certain extent, tensioning bolt 60 provides a fine adjustment for the extent of this impression, as indicated in Figure 3. Limit stop assembly 65, including an adjustable bolt and an abutment plate, prevents impression roller 41 from extending too far into the top of the wall. Assembly 65 thereby works in conjunction with the tensioning bolt 60 to provide additional adjustable support for the roller 41, to ensure its proper vertical position with respect to the wall.

The impression rollers may be constructed in a number of different ways. It is preferred to employ a rigid, inner form 57, such as that provided by a right-circular cylindrical drum. The drum may be hollow, solid, or filled with honeycomb or foam reinforcement material. The inner form 57 provides support and an arcuate shape for the resilient outer periphery 43, containing the pattern to be impressed in the concrete wall.

The resilient outer periphery 43 may be made from a moldable layer 58 of silicon-based material. It is preferred to use silicon-based material, or a functionally equivalent material, as it is curable from a liquid into a resilient layer. Through the use of a framed planar mold, any desired pattern may be formed in the lower surface of the mold. Then, the liquid silicon material, along with a curing agent, is poured into the mold. The liquid silicon is added to the fill the form until the layer is sufficiently thick and

a planar upper surface is formed. After the silicon layer has fully cured, it may be peeled away from the mold. Then, through the use of a spray or brush-applied adhesive, the planar upper surface of layer 58 is wrapped around the right-circular cylindrical outer surface 59 of inner form 57 (see, Figures 2 and 6). In this manner, layer 58 substantially covers the outer surface of the form 57.

5 Virtually any type of three-dimensional pattern may be formed in the layer 58. For example, a pattern representing a plurality of random stone shapes 61 separated from each other by respective mortar lines 62, is shown in the impression rollers in Figure 2. Of course the impression in the layer 58 is the negative of that which is impressed in the concrete wall. Thus, the random stone shapes 61 are depressed regions, and the mortar lines 62 are raised regions, as is most evident in Figure 6.

10 Other examples of three-dimensional patterns for the layer applied to an impression roller are shown in Figures 10-12. A layer 63, displaying a geometric pattern of straight, intersecting lines 64, is indicated in Figure 10. Depending upon the desired impression in the concrete wall, the lines in the layer may be either raised or depressed. The layer 66 shown in Figure 11, illustrates a brick 67 and mortar 68 pattern. To create a more realistic impression, the rectangular brick portions would be depressed and the dividing mortar portions would be raised, in the molded layer 66. In that way, the opposite three-dimensional pattern would be impressed in the concrete wall. Yet another example of a layer 69 is depicted in Figure 12. In this pattern, upper lines 71 are arranged in horizontal alignment, and lower lines 72 are arranged in vertical alignment. It should be apparent that by using such a system, where the pattern is molded into a layer forming the outer periphery of the impression roller, the greatest flexibility in
15
20 accomplishing the objects of the invention is achieved.

 However, alternative constructions for the impression roller may be used. Rather than applying a separate molded layer to the roller, a three-dimensional texture could be sprayed onto all or part of the roller. Three dimensional objects, themselves containing patterns or providing an object pattern, could be affixed to the outer surface of the roller, either mechanically or adhesively. Also, the impression

roller itself may be configured with flat sectors, or sections, to provide a three-dimensional pattern.

It has been determined that a resilient layer or coating is a significant feature for the impression roller of the present invention. Thus, irrespective of the configuration or construction of the roller, having a resilient outer periphery is necessary to form high-quality three-dimensional impressions in slip-formed walls. This stems primarily from the constituent makeup of the concrete 16 used in the slip-form process. As the concrete 16 is a very dry mix and includes more aggregate than a normal mix, an impression roller having a rigid outer periphery would tend to dislodge the aggregate and disrupt the integrity of the wall. The resilient layer, on the other hand, gives way when it encounters aggregate and smoothly rolls over such obstructions.

Returning now to Figure 2, a release agent spray bar 73 is shown. Spray bar 73 is located adjacent the discharge end 37 of the slip-frame assembly, so that a small amount of liquid release agent may be applied to all walls of the concrete wall 18 which are to be impressed with a pattern. (See, Figure 7). Without the use of a release agent, the dry concrete mix tends to adhere to the impression roller, and deface the surface of the concrete wall. Spray bars 73 are therefore used not only for each of the sidewall impression rollers 38 and 39, but also for the top wall roller 41. As shown in Figure 1, a release agent tank 74 and a pump 76 are mounted on the frame 12. Pump 76 provides a continuous supply of release agent to each of the spray bars.

An alternative to the use of a liquid spray release agent is shown in Figure 8. A roll 77 of a thin plastic film 78, such as VISQUINE, is mounted on a roll axle 78, secured between upper support arm 48 and lower support arm 49. The plastic film is captured between the impression roller and the concrete wall and sticks to the wet concrete after the impression is made. The film protects the outer periphery of the impression roller from being fouled during the impression process. Then, after the concrete in the wall has partially cured, the film is gently removed from the wall leaving the three-dimensional impression intact.

It should be apparent now that when the apparatus 11 is advanced forwardly, the support

system for the impression rollers is advanced at the same speed and in the same direction as slip form assembly 22. Owing to this forward advancement and the surface engagement between the outer periphery of each of the impression rollers and the exposed surface of the wet concrete, each of the impression rollers is caused to rotate. With this rotation of the impression rollers, successive portions of their outer peripheries impress successive portions of the concrete wall with the three-dimensional pattern.

In carrying out the method of the present invention, the following steps are followed for continuously impressing a three-dimensional pattern into a slip-formed concrete wall: (1) continuously slip-forming a concrete wall, in which the concrete wall has parallel side walls and a top wall, with the top wall spanning a transverse distance between the side walls; (2) maintaining a layer of resilient material having a three-dimensional pattern therein in an arcuate configuration, the resilient layer having an axis of rotation; (3) partially depressing the resilient layer into an exposed surface of the concrete wall just emerging from the slip form, providing surface engagement between the pattern and the exposed surface; (4) continuously rotating the layer of resilient material about its axis of rotation, at the same rate as the wall continues to emerge from the slip-form; and, (5) maintaining the axis of rotation in substantially parallel relation to the exposed surface, so that a successive portion of the pattern will impress a successive exposed portion of the concrete wall.

Figure 13 shows an implementation of the apparatus 11 of the present invention in which only a single sidewall impression roller 81 is employed. In this application, the three-dimensional pattern is only required to be impressed on one sidewall. In addition, the slip-formed concrete wall 82 is somewhat higher than that shown in the previous example. For these reasons, a slight modification is made to the slip-form assembly 83.

In the earlier described version of the invention, where an opposing pair of sidewall impression rollers 38 and 39 was employed, the lateral forces imposed against the wall 16 were opposing

and equal. However, the lateral forces applied by the single impression roller 81 against the sidewall of the concrete wall 82 are unopposed. This circumstance is exacerbated by the fact that wall 82 is fairly high, making lateral displacement of the wall under the forces of the impression roller even more likely. Through the simple expedient of extending the length of the opposing side wall form 84, a force equal and opposing to forces imposed by the impression roller 81 is presented. In other words, side wall form 84 extends outwardly and downstream from the main slip form assembly 83, a distance slightly past the point where the outer periphery of the impression roller 81 engages the exposed surface of the wall 82. In this manner, the wall 82 will be fully laterally supported during the impression process. In all other respects, the features and operation of the apparatus shown in Figure 13 is identical to that previously described.

Yet another specialized application of the apparatus of the present invention is shown in Figure 14. When a particularly tall slip-formed concrete wall 86 is to be made, a separate footing 87 is first poured, incorporating a reinforcement steel bar structure 88. Then, on a second pass of the apparatus, the concrete wall 86 is slip-formed so as to encompass and surround, the bar structure 88.

To provide additional strength and stability, it is desirable to form a flared-out skirt 89, at the base of the wall 86. Accordingly, slip-form assembly 91 includes a special extended side wall form 92 with an outwardly directed portion 93 to form one side of the side wall. The other side wall form (not shown), includes a complementary outwardly directed portion so as to form the other side of the skirt 89.

For the purpose of impressing a three-dimensional pattern in one side of this compound angled wall 86, a two-stage sidewall impression roller 94 is provided. Impression roller 94 includes an upper roller 96, which is elongated, and right-circular cylindrical in configuration. Roller 94 also includes a lower roller 97, which is frusto-conical in configuration. The rollers 96 and 97 are joined together, so as to rotate together at the same speed. As is evident from Figure 14, upper roller 96 impresses a three-dimensional pattern in the exposed surface of the upper vertical section of wall 86,

and lower roller 97 impresses a three-dimensional pattern on the exposed surface of the flared-out skirt 89. Of course, merely by adding another sidewall roller and a top wall roller, all three exposed surfaces of the wall 86 could be impressed with a three-dimensional pattern.

It will be appreciated, then, that I have described an apparatus and a method, for impressing aesthetically pleasing three-dimensional patterns in a slip-formed concrete wall.